

DPR Coating

Acrylic Coating



DESCRIPTION:

- 100% Acrylic-based coating available in textured or non-textured
- DPR (Dirt Pick-up Resistance): The surface of the coating hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold, and pollutants
- Excellent hiding power as well as flexibility and drying characteristics
- Integrally colored with high quality pigments
- For increased fade-resistance, use Parex USA ColorFast pigments.

USES:

- A protective and decorative exterior or interior coating over concrete, masonry, stucco, or acrylic-based textured finishes. Compatible with Parex USA finishes, may be applied over them
- To promote color uniformity of repaired and modified surfaces
- To color architectural details and graphics on any of the Parex USA Finishes and Coatings.
- Recoating existing EIFS or Stucco

COMPOSITION:

- Binder Base: 100% Acrylic
- Color: White or tinted to desired color
- Pigment based: Titanium dioxide
- Water base: VOC-Compliant. Meets SCAQMD Rule 1113 when using Parex USA Non-VOC Colorants.

PROPERTIES:

- Appearance: Flat, non-gloss, smooth finish
- Vapor Permeability: Water vapor permeable. Does not create a vapor barrier

PAREXUSA

COVERAGE:

Depending on the condition of the substrate and method of application, approximate coverage per pail is::

- DPR Coating
One coat: 1000-1200 ft²
(93-112 m²)

CONTAINER:

- 60 lb (27.7kg) net weight in plastic pails.
- Storage: Protect from direct sunlight and freezing at all times
 - Do not stack pails more than 3 pails high
 - Shelf Life: Reference Parex USA Expiration Date of Products Technical Bulletin.

DRYING TIME:

Approximately 1-4 hours depending upon temperature, humidity and substrate. Can be recoated after 8 hours. Allow minimum 5 days curing before gently washing the surface.

CLEAN-UP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Remove surface contaminants such as dust or dirt without damaging the substrate.
- For previously painted surfaces, all loose and chalking paint must be removed, and glossy surfaces dulled.
- New concrete and masonry must be clean and cured a minimum of 28 days.
- Check concrete surfaces for alkalinity and treat. Any form-release agents or bond breakers must be removed.
- Uneven concrete or masonry can be leveled with any Parex USA Basecoat & Adhesive or other suitable, compatible product.

- For interior drywall, prepare as for painting.
- Prime cementitious surfaces with Parex USA Primer, refer to Product Data Sheet.
- For additional options, contact Parex USA Technical Support.

MIXING:

- Use clean equipment for mixing and preparation
- Stir DPR Coating to a uniform consistency.
- Avoid creating air bubbles or foam.
- Stir occasionally as needed to keep uniformly mixed.

APPLICATION:

- Read the entire label before using this product
- Parex USA DPR Coating exhibits good surface coverage in single application. However, for most uncoated, unprimed surface of concrete, masonry, or drywall, two coats of the product may be required to obtain adequate hiding of the substrate and best performance.
- Parex USA DPR Coating is easily applied with either brush, roller, or suitable spray equipment. Apply as packaged. If necessary, add a small amount of clean potable water up to 8 oz (0.25L). Multiple coats may be needed to achieve desired results. Rolling/brush applications on smooth or fine textured surfaces can cause an orange peel texture.
- Add the same amount of water to each bucket. Also if different batches are used on the job box them for best color consistency.
- For spray applications, strain the material using a paint strainer.

LIMITATIONS:

- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Use only on surfaces that are sound, clean, dry, and free from any residue which may affect the ability of the DPR Coating to bond to the surface.
- Application in direct sunlight in hot weather may adversely affect aesthetics.
- Parex USA is not responsible for color correctness after finish has been applied.

WARNING

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- For more information on handling this product refer to its Safety Data Sheet (SDS). The most current SDS and Product Data Sheet (PDS) can be found on our website.
- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

PAREXUSA

Parex USA, Inc., a California Corporation
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
www.parexusa.com
866-516-0061 Tech Support: 800-226-2424