

314 Recoat Gel

Acrylic Coating



314 Recoat Gel

DESCRIPTION

- 100 percent acrylic-based non-textured semi-transparent coating.
- Recoats textured coatings without losing the structure of the finish.
- DPR (Dirt Pick-up Resistance).
 - The surface of the coating hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold, and pollutants.
- Integrally colored with high quality pigments.

USES:

- A protective and decorative exterior acrylic coating. Compatible with Parex finishes. May be applied over them.
- To promote color uniformity of repaired surfaces.
- Recoating existing textured finishes.
- To Revitalize or Increase the Mottled or Antique Look.

COMPOSITION:

- Binder base: 100 percent Acrylic.
- Water based: VOC compliant.
- Solids:
 - By weight: 58 percent
 - By volume: 47 percent
- Color: Must be tinted to desired color.
- Appearance: Semi-transparent.



314 Recoat Gel

Acrylic Coating

COVERAGE:

Depending on the condition of the substrate and method of application, approximate coverages is:

One coat: 800 - 1000 sq. ft.
(74 - 93 sq. m.) per pail

CONTAINER:

55 lb. (27.7kg) net weight in plastic pails.

- Storage: Protect from sun and freezing at all times.
 - Do not stack pails more than 3 pails high
- Shelf Life: One year if properly stored.

DRYING TIME:

Approximately 1-4 hours depending upon temperature, humidity and substrate. Can be recoated after 8 hours. Allow minimum 5 days curing before gently washing the surface.

CLEANUP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Textured Finishes: Remove surface contaminants such as dust or dirt without damaging the substrate.
- For additional options, contact ParexLahabra Technical Services Department.

MIXING:

- Use clean equipment for mixing and preparation.
- Stir Parex 314 Recoat Gel to a uniform consistency. Avoid creating air bubbles or foam.
- Stir occasionally as needed to keep pigments well mixed.

APPLICATION:

- Read the entire label before using this product
- Parex 314 Recoat Gel exhibits good surface coverage in single applications. However, two coats of Parex 314 Recoat Gel may be required to obtain adequate cover of the surface.
- Parex 314 Recoat Gel is easily applied with roller or suitable spray equipment. Apply Parex 314 Recoat Gel as packaged. If necessary, add a small amount of clean potable water: maximum 8 oz. (0.25L) per pail. Add the same amount to each pail for color consistency.

LIMITATIONS:

- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Use only on surfaces that are sound, clean, dry, and free from any residue which may affect the ability of the 314 Recoat Gel to bond to the surface.
- Application in direct sunlight in hot weather may adversely affect aesthetics.
- The product cannot be used to change colors from dark to light, but can be used to change colors from light to dark.

PAREX[®]
www.parex.com

Corporate Office
Parex USA, Inc.
4125 E. La Palma Avenue, Suite 250
Anaheim, CA 92807
(866) 516-0061

Plants
Redan, GA
Riverside, CA
French Camp, CA
Colorado Springs, CO
Albuquerque, NM
San Antonio, TX
Wilkes Barre, PA
Ft. Pierce, FL



MEMBER OF

EIMA