

PRODUCT DATA SHEET

Masonry Veneer Pointing Mortar

DESCRIPTION

- Pointing mortar for thin brick, natural stone and manufactured stone masonry veneers.
 - Easy mixing – only the addition of water is required
 - Easy application – creamy consistency
 - Mortar base to be used as-is or in junction with Parex USA dry color pigments
 - Part of the Parex USA MVS System
-

USE

For thin veneer mortar joints from 3/16" to 1 ¼"

COMPOSITION

Cement base binder with aggregates, pigments and additives.

PROPERTIES

- Compressive strength 28 days: 3000-3500 psi
 - Density: 1.9
-

CONTAINER

- 50 lb. bag (22.7 kg.) 48 bags per pallet
 - Shelf Life: Reference Parex USA Expiration Date of Product Technical Bulletin
-

WORKING TIME

1-2 hours

APPLICATION INFORMATION

SURFACE PREPARATION

Masonry veneer must be firmly attached to a sound substrate and MVS Adhesive must be cured a minimum of 24-48 hours before use of pointing mortar. Mortar joints should be uniform depth and width, free of loose debris, contaminants and excess mortar.

MIXING

- Use approximately 3 ½ quarts (3.4 liters) to 4 quarts (3.7 liters) of clean potable water for 50 lbs (22.7 kg) of MVS Pointing Mortar depending on the desired consistency and the way of application (trowel or grout bag). To avoid color variation use the same amount of water fore each bag
- Add MVS Pointing Mortar to a clean container and mix by hand or slow speed mixer slowly until a smooth consistency is achieved.
- Allow mortar to slake for 5 minutes then remix.

APPLICATION

- It is important to dampen the masonry veneer substrate prior to application to reduce the impact of surface porosity.
- Apply MVS Pointing Mortar to the masonry veneer mortar joint with either a trowel, pointing mortar tool or grout bag.
- Allow joint to firm and trowel or brush to desired finish.

LIMITATIONS

- MVS Pointing Mortar should not be installed when ambient temperature is below 40° F (4° C).
- Application should not be performed if rain is expected within 24 hours.
- Follow brick and stone manufacturer's recommendations.
- Acid should not be used to clean mortar joints.
- Brick and stone with high absorption, surface porosity may be prone to staining.
- Test in a small area to ensure desired results.

ENVIRONMENTAL HEALTH & SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets (containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**
- **FOR INDUSTRIAL USE ONLY**
- **FOR PROFESSIONAL USE ONLY**

Prior to each use of any product of Parex USA, the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at parexusa.com or by calling Parex USA Technical Service Department at 1-800-226-2424. Nothing contained in any Parex USA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each Parex USA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the Parex USA product.

Parex USA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Parex USA, Inc., a California Corporation

21507 Eastridge Avenue

Riverside, CA 92507

www.parexusa.com

866-516-0061

Tech Support: 800-226-2424

© Parex USA, Inc. APRIL 2020 | PU MVS PM DS 0420

PAREXUSA